

<p>Overview</p>	<p><i>Structure Deck</i> 5 x leg frame heights, 1 x standard brace rail and leg extensions 1 x standard & Tri-Dek</p> <p><i>Handrails Step</i> Horizontal safety option Step units can create flights at 150mm increments from 300mm upwards</p> <p><i>Step Rails</i> 150mm increments</p>
<p>Frame</p>	<p><i>Leg Frame Height</i> Standard heights include 300mm/450mm/600mm/750mm/900mm/1050mm. Each frame can be used in conjunction with each other to produce level and multi height layouts.</p> <p><i>Leg Frame</i> 45mm x 45mm x 2.5mm wall ERW steel tube</p> <p><i>Brace Rail</i> 40mm x 70mm x 2.5mm wall ERW steel tube</p> <p><i>Finish</i> Gold passivated bright zinc plate</p> <p><i>Foot Bungs</i> Low Density Polyethylene</p>
<p>Deck</p>	<p><i>Size</i> 1209mm x 1209mm x 30mm</p> <p><i>Material</i> 8mm spruce core with 2 x 6mm BB/BB birch plywood</p> <p><i>Finish</i> UV coated with slip resistant acrylic lacquer as standard. Other options include carpet and black emulsion finish.</p> <p><i>Versatility</i> Can be reversed.</p>
<p>Step/Handrails</p>	<p><i>Size/Material</i> Ø38.01mm x 2.03mm wall ERW steel tube</p> <p><i>Height</i> Nominal 1100mm above deck</p> <p><i>Finish</i> Gold passivated bright zinc plate/clear passivated, bright zinc or epoxy powder coated in a range of colours (optional).</p> <p><i>Attachment</i> Connects into frame with brace and pin and corner brace when necessary.</p>
<p>Steps</p>	<p><i>Materials</i> 15mm BB/BB birch plywood/Mild steel framework</p> <p><i>Height</i> Step modules in 150mm rises to suite stage</p> <p><i>Finish</i> UV coated with slip resistant acrylic lacquer as standard. Other options include carpet or black grade emulsion / Gold passivated bright zinc plate as standard.</p>

NB Specifications cover all options and reference should be made to the specific equipment as detailed in the quotation

**Multi-Dek
Technical Specification**



<p>Certification</p> <p><i>Structure</i></p> <p><i>Carpet</i></p> <p><i>Skirting & back drapes</i></p> <p><i>Vinyl</i></p>	<p>Temporary Demountable Structures: 2nd Edition BS6399: 1996: Part 1: Loadings for Buildings.</p> <p>Heckmondwike 'Iron Duke' heavy contract broadloom carpet, 5mm, Tested to BS5287 for flammability</p> <p>Bournemouth Curtains Ltd. Accolade. Inherently flame retardant 'dim out' curtaining conforming to BS5867 Part 2:B</p> <p>Rosco floors, black/grey, 1.3mm, fire resistance NFPA701</p>
<p>Miscellaneous</p> <p><i>Bespoke</i></p> <p><i>Bespoke Accessories</i></p> <p><i>Guarantee Service</i></p>	<p>Multi-Dek can be adapted to fit perfectly into a specific space, whether the space is an irregular shape, has an uneven floor or there are obstacles such as pillars, steps or supports.</p> <p>Different carpet finishes, split level, cable ports, fascia panels, special trims to deck edges and step treads.</p> <p>All standard components are guaranteed for 5 years</p> <p>Commissioning of equipment, user training and O&M manuals provided where necessary</p>

NB Specifications cover all options and reference should be made to the specific equipment as detailed in the quotation

